

IN THE CLAIMS

1 (Amended). A high intensity discharge lamp assembly, comprising:

- gib-1
- a) a high intensity discharge lamp comprising a hermetically sealed glass envelope containing a mixture of ionizable elements and/or compounds;
 - b) a sealed ballast container mounted adjacent to said glass envelope;
 - c) an electronic ballast contained in said container, said ballast having an input and an output;
 - d) an anode disposed in said envelope and electrically coupled to one pole of said ballast output;
 - e) a cathode disposed in said envelope and electrically coupled to another pole of said ballast output; and
 - f) coupling means for coupling said input of said ballast to a DC power source; and
 - g) heat sink means for dissipating heat from said ballast.
- ay

2 (Amended). A lamp assembly according to claim 1, further comprising:

- h) a waterproof protective container covering said envelope, said waterproof protective container having a transparent window.

3 (Amended). A lamp assembly according to claim 1, further comprising:

h) a waterproof protective container covering said envelope and said ballast container, said waterproof protective container having a transparent window.

3.4 (Amended). A lamp assembly according to claim 1, wherein:

94
Cond
said coupling means is a cable with a wet pluggable plug at one end for coupling/uncoupling to/from a battery pack while under water.

8.6 (Amended). A lamp assembly according to claim 1, wherein:

as
said ballast container is potted with a thermally conductive epoxy, said epoxy serving as said heat sink means.

8 (Amended). An underwater lighting system, comprising:

- 90
92
96
- a) a high intensity discharge lamp comprising a hermetically sealed glass envelope containing a mixture of ionizable elements and/or compounds;
 - b) a sealed ballast container mounted adjacent to said glass envelope;
 - c) an electronic ballast contained in said container, said ballast having an input and an output;
 - d) an anode disposed in said envelope and electrically coupled to one pole of said ballast output;

- e) a cathode disposed in said envelope and electrically coupled to another pole of said ballast output;
- f) a battery pack having a power coupling; and
- g) a cable coupled to said input of said ballast to said power output of said battery pack; and
- h) heat sink means for dissipating heat from said ballast.

8. ⁷ (Amended). An underwater lighting system according to claim 8, further comprising:

- Ab
Cox
- i) a waterproof protective container covering said envelope, said waterproof protective container having a transparent window.

10 (Amended). An underwater lighting system according to claim 8, further comprising:

- B
- i) a waterproof protective container covering said envelope and said ballast container, said waterproof protective container having a transparent window.

11. ⁷ (Amended). An underwater lighting system according to claim 8, wherein:

97

said ballast container is potted with a thermally conductive epoxy, said epoxy serving as said heat sink means.